

Data Sheet

Model: BMF11/3

Laboratory Ashing Furnace



INTRODUCTION

The **BMF11** Laboratory Ashing furnace offers a choice of chamber capacities ranging from 3 & 7 litres in standard versions. Other chamber capacities/volumes are offered in custom-built models.

The **BMF11/3** Laboratory Ashing furnace has a 3-liter capacity.

SPECIFICATIONS

Maximum Temperature: 1100°C

Maximum Continuous Temperature: 1050°C

| Chamber dimensions (mm): 90 x 150 x 235 (H x W x D)

| Wire wound muffle

| Compact bench mounted design

| Designed for Ashing applications

| Energy efficient, high quality, low thermal mass insulation

| The BMF model provides a pre-heated airflow system and a large metal chimney to ensure good combustion conditions within the chamber and improved process fume removal from the chamber

| Insulated door opens upwards and outwards keeping the hot face away from the operator

| Vertically lifting door keeps the hot surface away from the user

| High end Microprocessor PID controller

| Hard ceramic base is fitted as standard



BMF11/3

*The image shown above is for representational purpose only.

| **External Dimensions (mm):** 593 x 400 x 505 (H x W x D)
(Indicative)

| **Net Wt.:** 36 kg

| **Power Supply:** 230V– 1 Phase

| **Energy rating:** 2.0 kW

OPTIONS

| Independent Over-temperature protection system

| Multi segment, multi program storage controllers

| Powered exhaust, Chimney with fan

| Crucibles (Alumina/Fused Silica)

| Lids (Required while cooling)

| Sample Trays

| Tray Loading Handles

Elite Thermal Systems Limited

Units F1-F2 and F3, Welland Business Park, Valley Way, Market Harborough. Leicestershire. LE16 7PS, UK

Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com