





POSA Chemical Industries Co. (Public Joint Stock)



Our Horizon

- To maximize sustainable value and performance for the shareholders, clients, employees and the society.
- To achieve sustainable economic success.
- To achieve sustainable development and profitable growth.

We Care and value

- Environmentally friendly products.
- Clear competitive advantage.
- Clearer strategic focus.
- Reliability and safety.
- Quality and high-speed response.
- Flexibility and innovation.

POSA (PJS) is located in the gas and oil-rich area, southeast of Iran. Surrounded by 7 hectares of green plantation. Land transport as well as on the way operative railroad facilities to our biggest Bandar Abbas sea port has made a unique opportunity for POSA to improve and develop her international exportation market.

Overview

POSA Chemical Industries. Co. Plants of FA 37-42 Percent, Hexamine min 99.5 Percent, Paraformaldehyde min 96 Percent Powder, benefits a well managed architectural backbone based on BIP, England and Joseph Meisener, Germany established in 1983 and put into production in the year 1990.



Current Situation

Thanks god that by now POSA Chem. IND. Co has the ability to design, construct and commission 100 TPD Formalin plants along with silver regeneration technology and other derivatives plants at any place inside or outside Iran.

Production Units

Sina and her affiliated companies produce following chemicals:

- A) Formalin 37–42 Percent
- B) Hexamine Min. 99.5 Percent
- C) Paraformaldehyde 96 Percent Powder

A) Formalin (CH₂O)

Commercially, formaldehyde is marked chiefly in the form of aqueous solutions containing 37-52 percent by weight dissolved formalin.

Higher concentration of formalin contains sufficient methanol to prevent precipitation of polymer under ordinary conditions of transportation and storage.

UN No.	2209	
IMDG Code	8176-1	
IMCO Class	8	

Capacity: 70,000 MTPY



CAS Number	50-00-0

EC	Number	200-001-8

A-1) Specification:

Spec.	Result	
Appearance	Colorless liquid	
Formaldehyde wt%	37 - 42	
Methanol * wt%	Min. 3	
Acidity wt%	Max. 0.05	
PH	2.4 - 4	
SPG gr/cm ³	1.09 - 1.12	
Iron Content	Nil	

^{*} Higher Methanol content can be adjusted upon request. (Max. 8.5 wt%)

A-2) Application:

- Polyacetal
- Amino Resins
- Phenolic Resins
- MDI
- Pentaerythritol
- Synthetic Rubber
- TMP,TME,NPG
- Paraformaldehyde
- Hexamethylenetetramine

A-3) Storage:

If kept at room or at slightly higher temperature in non corrosive tank, it will avoid polymerization and contamination.

A-4) Packaging:

- In 220 Liter net HM-HDPE drums, 4 drums on pallet, 20 pallets = 18.4 MT net in 40 FCL.
- In 24-25 MT net ISO tanks.



B) Hexamine $(C_6H_{12}N_4)$

Capacity: 4000 MTPY

Hexamine is formed by the reaction of formaldehyde and ammonia, it reacts as formaldehyde in many instances and therefore may be is regarded as a special form of formaldehyde from the standpoint of use.



5H3

CAS Number 10	00-97-0
---------------	---------

EC	Number	202-905-8
	Mullipel	404-703-0

Molecular Weight	gr	140.2
Melting Point	°c	270
Density	1.33	
Bulk density	0.7 - 0.8	
a	Water wt.9	81.3
Solubility In 20 °c	Methanol wt.%	7.25
III 20 C	Ethanol wt.%	2.89
	Acetone wt.%	0.65



Specification:

B-1-1) Hexamine Unstabilized

Spec.		Result	
Appearance			
Purity	wt.%	Min. 99.5	
Ash Content	wt.%	Max. 0.03	
Humidity	wt.%	Max. 0.25	
Ammonia	wt.%	Max. 0.02	
Formaldehyde	wt.%	Max. 0.02	
Chloride		Nil	
Sulfate		Nil	
Heavy metals		Nil	
PH (10% Aq. soln.)		8 – 9.5	
Particle Size	μ	80 - 800	

B-1-2) Hexamine Stabilized (0.5 – 1.5 Wt% Silica) *

Spec. Status	
Appearance	White Crystalline Powder
Purity wt.%	Min. 98 – 99 %
Ash Content wt.%	Max. 0.53- 1.53
Humidity wt.%	Max. 0.25
Ammonia wt.%	Max. 0.02
Formaldehyde wt.%	Max. 0.02

Chloride	Nil
Sulphate	Nil
Heavy metals	Nil
PH (10% Aq. soln.)	8 – 9.5
Particle Size μ	80 - 800

^{*} Benzoic, Salicylic,...., and their mineral salts can be replaced by request

B-2) Application:

- Hardener in synthetic resins
- Pharmaceuticals
- Agriculture
- Leather and Textile
- Explosives
- Rubber
- Photography
- Organic chemicals
- Paper
- Oil
- Metal Industry

B-3) Storage:

Hexamine is sensitive to humidity, but is not a hygroscopic substance. It may cake at low humidity, excess pressure and temperature. Suitable storage condition is recommended.

B-4) Packaging: (Group III)

• In 25 kg net PP/PE or a 3 layer pressed Polyethylene bag, 40 bags on pallet, 20 Pallets = 20 MT in 20 FCL.

C) Paraformaldehyde H-(CH₂O)_n-OH

Capacity: 10000 MTPY

Paraformaldehyde is the commercial linear polymer of formaldehyde. It is the mixture of low molecular weight of polyoxymethylene glycols. The polymer behaves chemically as a solid form of formaldehyde. It is much more stable and suitable for storage and economical transportation.

	CAS Numb	er	30525-89-4
			_
	EC Number	er	200-001-8
cking Code			

C-1) Specification:

Characteristic	Actual Value
Appearance	White Powder
Color	Sol. 10 wt. % (Aq) 20 Apha
Aldehyde Content (wt%)	Min. 96
Melting Range (°C)	120 – 170
Acidity (As formic acid) (wt %)	Max. 0.02
Water Insoluble (wt %)	Max. 0.1
pH of 10% aqueous solution	5-7
Iron content (ppm)	15 ± 5
Ash Content (wt %)	Max. 0.1
Bulk Density (g/cm ³)	0.8-0.9
Flash point (°C)	71
Moisture (wt %)	Max. 1
Mesh Size 100-3000 Micron 0.1-3.0 mm US Mesh: 6-140	

C-2) Application:

- Thermosetting resins
- Coating resins, Enamels
- Glyphosate
- Disinfectants, insecticides & pesticides
- Fungicide and bactericide
- Ion exchange resins
- Abrasives
- Pharmaceuticals
- Textile dyes & special plasticizers
- Automotive paints and Stoving finishes
- Electro coatings and water born finishes
- Ink industries

C-3) Storage:

In tightly closed bags prevented from direct sunlight and humidity.

C-4) Packaging:

- In 25 kg net PP/PE or 3-layer pressed Polyethylene bag, 40 bags on pallet, 20 Pallets = 20 MT in 20 FCL.
- 1000 kg Jumbo Bags, Stuffing: one Jumbo bag with pallet on top of the other Jumbo bags without pallet / 2 x 10 = 20 jumbo bags /20' FCL.
- 500 kg Jumbo Bags , Stuffing: Two Jumbo bags with pallet / 2 x 20 = 40 jumbo bags /20' FCL.