

**PRODUCT LINE**Surface Wellhead | Drilling  
Wellheads**PRODUCT**

G-25 Stacker Drill-Thru System



Streamline your operations with efficient drilling, casing, and cementing—all without breaking the BOP stack. Built for performance, precision, and adaptability.

**The G-25 Stacker Drill-Thru System** saves you time by facilitating drilling, running, and cementing intermediate and production casing, while eliminating the need to break the BOP Stack to install an intermediate casing spool.

### Options

- BOP Quick Connect Adaptor available for batch drilling operations.
- Available with conventional lockdown screws or internal latch retention for hangers and pack-offs.
- Land production casing in a fluted mandrel hanger, solid mandrel hanger, or casing slips.
- Available for 2, 3, and 4 string casing programs.
- Slip-on weld or threaded box bottom connection compatible with a landing base.
- Option to land production casing or tie-back in a nested bowl.
- Contingency casing slips and pack-off assembly provided when casing won't go to the bottom.
- Ability to run control/instrumentation lines within the system upon request.

### Specifications

- Available Sizes: 11" and 13"
- Pressure Rating Range: 5,000 PSI - 15,000 PSI
- Upper Flange Size: 7-1/16" – 21-1/14"
- Surface Casings: 7" – 20"
- Temperature Range: -75F (K) to +250F (V) (Can be combined)
- Trim Levels: AA – EE (FF and HH offered in certain use cases)
- PSL Ratings: 1, 2, and 3
- Hanger Threads: Standard and Premium Threading available

