

The **Innovex B3 Frac Plug**, with its industry-leading dissolvable technology, offers a dependable, cost-effective dissolving frac plug optimized for zonal isolation. It provides operators with easier clean-outs, risk mitigation, and, most importantly, valuable time savings, making it a beneficial choice for their projects and ensuring efficiency and productivity.

This frac plug integrates features from the highly successful B2 Slim dissolvable frac plugs, which were launched in early 2023. It is engineered to meet the same rigorous specifications as the existing B2 and ensures compatibility with current wireline adapter kits.

Features and Customer Benefits

- Sealing effectiveness optimized for zonal isolation
 - Maximized radial engagement force
 - Proven seal with ovality casing
 - Validated with downhole imaging
- Optimized deployment
 - Maximum RIH durability
 - Pump down ring (PDR)
 - Reduce outside diameter (OD)
- Material options
 - Proprietary dissolvable material options suitable for all well environments
 - Ultra-low temperature, freshwater alloy blend, field proven in 120°F freshwater
 - Fully dissolvable sealing element and PDR



Dimensional Data	Value	Unit	Value	Unit
Casing Size	6.000	inches	152.40	mm
Weight	22.3 to 26	ppf	33.19 to 38.69	kg/m
Setting Tool	Size 20 E-4 WLPSA			
Setting Load	49,000 ± 10%			
Max OD	4.880	inches	123.95	mm
Min ID	1.094	inches	27.79	mm
Run in Length	8.870	inches	225.30	mm
Set in Length	5.000	inches	127.00	mm
Temperature Rating (Degradable Element)	250	°F	121	°C
Pressure Rating	10,000	psi		
Plug Material	Fast or Standard Dissolve Components			
Material SG	1.7 to 1.8			
Ball OD	1.580	inches	40.13	mm
Pump Down Rate	12 to 18 bpm			
Pump Down Speed	300 to 550 fpm			