

Data Sheet

Model: VMF/ISO

Volatile Matter Furnace



INTRODUCTION

The VMF/ISO is engineered for volatile matter analysis in compliance with ISO 562 and EN ISO 22167 standards. It features precise temperature control and quick response times, ensuring both accuracy and efficiency in determining the volatile matter content in coal, coke & solid recovered fuels (SRF).

SPECIFICATIONS

Maximum Temperature: 1100°C

Maximum Continuous Temperature: 1050°C

| Chamber dimensions (mm): 110 x 200 x 254 (H x W x D)

| Open spiral elements located in the chamber roof and under the hearth supported in low thermal mass insulation ensure rapid heating required for analysis as per ISO 562 and EN ISO 22167

| The chimney has a provision to restrict airflow/convection through the furnace

| Provision for inserting external thermocouples (Three positions) to check the temperature under the crucibles is provided

| Vertical lifting door keeps the hot face away from the operator when the door is opened

| Positive break door safety switch isolates heating elements from power supply when door is opened

| High-end micro-processor PID controller



VMF/ISO

| **External Dimensions (mm):** 727 x 582 x 645 (H x W x D)
(Indicative)

| **Supply / Power:** 230V– 1 Phase – 3000 Watts.

OPTIONAL FEATURES

| Multi segment, multi program storage controllers with audible alarm & timer

| 4, 6 & 9 crucible racks with loading handle

| Crucibles and lids as per ISO 562 and EN ISO 22167

| Calibrated thermocouple probe with digital indicator

Elite Thermal Systems Limited

Units F1-F2 and F3, Welland Business Park, Valley Way, Market Harborough, Leicestershire LE16 7PS, UK

Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com