

Technical data:

Venterra inter-row hoe

Model	Venterra 1K	Venterra 2K	Venterra VR 4
Working width (m)	1.30–4.20	4.50–6.75	7.20–12.80
Row spacing (cm)	flexible from 12.5 cm		
Frame height in the field	(M) 80 cm	(M) 80 or (L) 100 cm	(M) 80 cm
Transport width	3.00	2.95	2.99
Weight (75 cm rows) (kg)	560*	1,268*	2,876/3,232**
Front mounting	✓	✓	
Rear mounting	✓	✓	✓
Camera control	✓	✓	✓
Part-width section control	✓	✓	✓
Linkage	Cat. 2 or 3		Cat. 3
Power requirement (kW/hp)	44/60	60/80	from 118/160

*Rear mounting with Type KPP-M parallelogram and a row spacing of 75 cm

**Venterra VR 4 (9 m)/Venterra VR 4 (12 m) rear-mounted with an integrated shift frame, Type KPP-M parallelogram and a row spacing of 75 cm

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.