



Cotton SP

12-0-42

PRODUCT DESCRIPTION: Speedfol® Cotton SP contains nitrate nitrogen, potassium, boron, and manganese, four essential elements for improved boll development and lint quality. Speedfol® Cotton SP has an acidifying effect on the pH of the spray water. A lower pH will improve the stability of the majority of pesticides, which results in higher pesticide effectiveness.

GUARANTEED ANALYSIS

Total nitrogen (N).....	12%
12.0% Nitrate Nitrogen	
Soluble Potash (K ₂ O).....	42%
Boron (B).....	1.0%
Manganese (Mn).....	0.2%

Derived from: Potassium Nitrate, Manganese Sulfate, Boric Acid. **F1367**

RECOMMENDATION AND GUIDELINES FOR FOLIAR SPRAYINGS

1. For 1 acre: dissolve 10 lb Speedfol® Cotton SP/acre in at least 10 gallons of water.
2. Add Speedfol® Cotton SP when the tank is half filled with water and stir as remainder of water is added until Speedfol® Cotton SP is dissolved.
3. Apply 4 times after the first flower appears with intervals of 7 to 10 days.
 - a. Apply in total 40 lbs Speedfol® Cotton SP/acre.
 - b. An early start (begin flowering) with the applications is important, when the leaf has not formed a thick waxy layer yet.
4. Apply early in the morning or late in the afternoon.
5. Make a jar test to check the compatibility with pesticides.
6. Make a test with different concentrations of Speedfol® Cotton SP to determine when leaf burning takes place.
7. pH levels of the final tank mix solution below 4 may cause scorching.

DANGER

May intensify fire, oxidizer. May damage fertility. May damage the unborn child. Keep

away from flammable/combustible/reducing materials. Wear protective gloves/ protective clothing/ eye protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. In case of fire: use any suitable mean for extinguishing surrounding fire. Spray water for small fires. For large fires flood with abundant water. If exposed or concerned: get medical advice/attention. Store locked up. Dispose of contents/container according to local/state regulations.



IN CASE OF EMERGENCY CALL CHEMTREC For Hazardous Materials [or Dangerous Goods] Incidents ONLY (spill, leak, fire, exposure, or accident) 1-800-424-9300

For additional information, see Safety Data Sheet (SDS) for this product.



UN1486 OXIDIZING

SOLID, N.O.S (Potassium Nitrate Mixture)



Guaranteed by:

SQM North America Corporation
2727 Paces Ferry Rd, Building
Two, Suite 1425
Atlanta, GA 30339. USA
(800) 234-9376
sqmnutrition.com

Net Weight:
25 lbs